



ENHANCED RELIABILITY

Low Maintenance gauge operated by anyone in less than 10 mins.

METROLOG BREAKTHROUGH

High-temperature electronic board with redundant memories.

APPLICATIONS

For DST, coil tubing and all slim-hole operations.

SPECIFICATIONS*

PRESSURE	<i>PiezoResistive Sensor</i>
Range	0-15000 psi (0-1000 bar)
Accuracy	± 0.05% FS
Resolution	<0.05 psi (<0.003 bar)
TEMPERATURE	<i>PT100</i>
Range	0 to 300 °F (-20 to 150 °C)
Accuracy	± 0.6 °F (± 0.3 °C)
Resolution	<0.01 °F (<0.005 °C)
MECHANICS	
OD	3/4" (19 mm)
Length	10" (25.4 cm)
Weight	0.5 lbs (250 g)
MEMORY	
Capacity	4 200 000 data points of pressure and/or temperature
COMPUTER AND SOFTWARE	
Programming Modes	Conventional, Advanced
Parameters	1s-18h Scanning Rate, Time delay, Pressure start (Trigger, Threshold)
Windows	Compatible with Windows 2000/XP/Vista/7/8
Connector	USB
BATTERY TYPE	
X15	Cumulative operating time up to 180 days.

* Enhanced specifications available on demand

Metrolog, a Sercel Brand

1110 Avenue l'Occitane, Technoparc, Bât.2, C.S. 17619. 31676 Labège Cedex FRANCE

Telephone: (33) 5 61 34 80 74. Fax: (33) 5 61 20 41 31. E-mail: sales@metrolog.com

www.metrolog.com

Sercel

S.A. au capital de 2 000 000 €. Siège Social: 16 rue de Bel-Air 44470 Carquefou.

378.040.497 R.C.S. Nantes. Code APE 2651B

www.sercel.com

Printed in France. © Sercel 08/15 - Information subject to change without notice. TSO_059_A