IQUARTZ5-XHT

NEW SLIM QUARTZ CRYSTAL GAUGE FOR APPLICATIONS UP TO 392°F/200°C

ENHANCED RELIABILITY

Low Maintenance gauge operated by anyone in less than 10 mins. Laterally locked battery avoids disconnection in operation. Metal-to-metal seal for better protection of the electronic board.

METROLOG BREAKTHROUGH

External communication port reduces maintenance cost and time. Smart battery system displays the remaining power of your cells. High-temperature electronic board with 4 times redundant memories.

APPLICATIONS

For very accurate reservoir monitoring, static/dynamic gradient and build-up. Also for pulse/interference tests and long term jobs. Extra Slim gauge for DST, coil tubing, slickline and slim-hole operations.

SPECIFICATIONS

PRESSURE	Quartz Sensor
Range Accuracy Resolution	0-10000 up to 0-20 000 psi (0-700 to 0-1 400 bar) ± 0.02% FS <0.01 psi (<0.001 bar)
TEMPERATURE	Quartz Sensor
Range Accuracy Resolution	0 to 392°F (-20 to 200°C) ± 0.3°F (± 0.15°C) <0.01°F (<0.005°C)
MECHANICS	
Material OD Length Weight Threads Bottom nose	High-Quality Inconel suitable for sour service (H ₂ S, CO ₂ , acid) ³ ⁄ ₄ " (19 mm) 20" (51 cm) for Insert, 24" (61 cm) for Slickline Version 1 lbs (500 g) 5/8" 11 UNC (pin up x box down) or non threaded housing (Insert) ¹ ⁄ ₄ " NPT (female)
MEMORY	
Capacity	2 100 000 data points of pressure and/or temperature
COMPUTER AND SOFTWARE	
Programming Modes Parameters Windows Connector	Conventional, Advanced 1/100s-18h Scanning Rate, Delay, Pressure start (Trigger, Threshold) Compatible with Windows 2000/XP/Vista/7 RS232/USB
BATTERY TYPE	
Z20/2Z20/Z15E/LZ15E	



Metrolog

SERCEL BRAND





toga.

Metrolog, a Sercel Brand

1110 Avenue l'Occitane, Technoparc, Bât.2, C.S. 17619. 31676 Labège Cedex FRANCE Telephone: (33) 5 61 34 80 74. Fax: (33) 5 61 20 41 31. E-mail: sales@metrolog.com www.metrolog.com

Sercel

S.A. au capital de 2 000 000 €. Siège Social: 16 rue de Bel-Air 44470 Carquefou. 378.040.497 R.C.S. Nantes. Code APE 2651B www.sercel.com

Printed in France.[©] Sercel 06/13 - Information subject to change without notice. TDSO_049_B